



BRAMCO CONTROLS DIVISION, LEDEX INC.

College and South Streets, Piqua, Ohio 45356 • Phone 513-773-8271

STANDARD FREQUENCY CHART

DATA SHEET 19

The frequencies listed below have been established to allow adequate separation and minimum harmonic relationship for use in multiple frequency systems.

FREQ. C.P.S.	EIA CODE	FREQ. C.P.S.	EIA CODE	FREQ. C.P.S.	EIA CODE	FREQ. C.P.S.	EIA CODE
67.0	L 1	192.8	7A	410.8	114	810.2	157
71.9	L 2	203.5	M1	422.1	145	832.5	127
77.0	L 3	210.7	M2	433.7	115	855.2	158
82.5	L 4	218.1	M3	445.7	146	879.0	128
88.5	L 4A	225.7	M4	457.9	116	903.0	159
94.8	L 5	233.6	M5	470.5	147	928.1	129
100.0	1	241.8	M6	483.5	117	953.7	160
103.5	1A	250.3	M7	496.8	148	979.9	130
107.2	1B	258.8	136	510.5	118	1006.9	161
110.9	2	266.0	106	524.6	149	1049.6	131
114.8	2A	273.3	137	539.0	119	1084.0	P
118.8	2B	280.8	107	553.9	150	1120.0	S11
123.0	3	288.5	138	569.1	120	1190.0	S12
127.3	3A	296.5	108	582.1	H	1220.0	S2
131.8	3B	304.7	139	600.9	121	1265.0	S14
136.5	4	313.0	109	617.4	152	1291.4	S3
141.3	4A	321.7	140	634.5	122	1320.0	S15
146.2	4B	330.5	110	651.9	153	1355.0	S16
151.4	5	339.6	141	669.9	123	1400.0	S17
156.7	5A	349.0	111	688.3	154	1430.5	S7
162.2	5B	358.6	142	707.3	124	1450.0	S18
167.9	6	368.5	112	726.8	155	1500.0	S20
173.8	6A	378.6	143	746.8	125	1520.0	S9
179.9	6B	389.0	113	767.4	156	1550.0	S21
186.2	7	399.8	144	788.5	126	1600.0	S22

MODEL	RECOMMENDED RANGE	TOTAL RANGE
RD 10, RE 10	67-300 (39)	67-1600 (100)
RD 1, RE 1	300-600 (25)	300-1600 (61)
RD 5	200-600 (38)	100-1000 (77)
RD 7	150-500 (40)	150-700 (52)

Figures in parentheses are the number of standard frequencies possible within the listed range.